

4-Line Low Capacitance TVS Diode Array

Features


- IEC 61000-4-2 (ESD) $\pm 30\text{kV}$ (air), $\pm 30\text{kV}$ (contact)
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 25A (8/20 μs)
- Low Capacitance: 1.5pF typical (I/O to I/O)
- Low leakage current
- Operating Voltage: 5V
- Low clamping Voltage
- Up to four data lines and one power line protects

Applications


- USB 2.0 Power and Data lines protection
- Digital Visual Interface (DVI)
- Monitors and Flat Panel Displays
- Video Graphic Cards
- Notebook and PC Computers

Mechanical Characteristics

- Package: SOT-23-6L
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- RoHS Compliant



Circuit and Pin Schematic

**Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ Unless otherwise noted)**

Parameter	Symbol	Value	Unit
Peak Pulse Power ($tp = 8/20\mu\text{s}$)	P_{PP}	500	W
Peak Pulse Current ($tp = 8/20\mu\text{s}$)	I_{PP}	25	A
ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 30	KV
ESD per IEC 61000-4-2 (Contact)		± 30	
Operating Temperature Range	T_J	-55 to + 125	°C
Storage Temperature Range	T_{STG}	-55 to + 150	°C

Electrical Parameters ($T_A = 25^\circ\text{C}$ Unless otherwise noted)

Symbol	Parameter	
I_{PP}	Reverse Peak Pulse Current	
V_C	Clamping Voltage @ I_{PP}	
V_{RWM}	Reverse Stand-Off Voltage	
I_R	Reverse Leakage Current @ V_{RWM}	
V_{BR}	Breakdown Voltage @ I_T	
I_T	Test Current	
I_F	Forward Current	
V_F	Forward Voltage @ I_F	

Electrical Characteristics ($T_A = 25^\circ\text{C}$ Unless otherwise noted)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Reverse Standoff Voltage	V_{RWM}	Any I/O pin to ground			5	V
Reverse breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$, Any I/O pin to ground	6			V
Reverse leakage current	I_R	$V_{RWM} = 5\text{V}$, Any I/O pin to ground			1	μA
Clamping Voltage	V_C	$I_{PP} = 1\text{A}$ ($t_p = 8/20\mu\text{s}$), any I/O pin to ground			12	V
Clamping Voltage	V_C	$I_{PP} = 25\text{A}$ ($t_p = 8/20\mu\text{s}$), any I/O pin to ground			20	V
Junction capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$, between I/O pins		1.5		pF
Junction capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$, any I/O pin to ground		3.0	5.0	pF

Note 1: I/O pins are Pin 1, 3, 4 and 6

Typical Performance Characteristics ($T_A = 25^\circ\text{C}$ Unless otherwise noted)




Figure 1. Junction Capacitance vs. Reverse Voltage




Figure 2. Peak Pulse Power vs. Pulse Time




Figure 3. Clamping Voltage vs. Peak Pulse Current




Figure 4. Power Derating Curve




Figure 5. 8 X 20μs Pulse Waveform




Figure 6. ESD Clamping Voltage
8 KV Contact per IEC61000-4-2

Suggested PAD Layout

Symbol	SOT-23-6L	
	(mm)	(inch)
A	1.10	0.043
B	0.60	0.024
C	1.90	0.075
D	2.50	0.098
E	3.60	0.142

Marking Code

Part Number	Marking Code
SC05Y4UTS	SRV05
SRV05 = Device Marking Code	

Ordering information

Part Number	Package	Base qty	Reel Size	Delivery mode
		(pcs)	(inch)	
SC05Y4UTS	SOT-23-6L	3,000	7	Tape and reel